ACCESS THE FUTURE FACIAL RECOGNITION ACCESS CONTROL

Your face is your key

OAHFACE

Introducing the world's first app based facial recognition access system. NoahFace Access is the faster, smarter and easier way for businesses to manage access of employees and visitors. Installing is easy as it retro fits onto any existing single or multi door set-up, with or without a control system.

How it works

NoahFace Access operates as a tablet, mounted adjacent to a door that evaluates and approves authorised faces. Based on pre-configured rules, the receiver then operates the controlled door. It does this either directly (in a stand-alone configuration), or via the existing access control system (in an integrated configuration).

The configured access rules include support for day-of-week, time of-day and even capability for different identification requirements at different times. For example, you can allow fast and convenient facial recognition access during business hours, while requiring a passcode or even an access card outside of these hours.

A photographic record of all access attempts is stored in an event log so you can examine later if needed. These logs can be exported for longer terms storage and reference.





www.noahface.com/access



Key Parameters

Access Bluetooth Receiver 12V DC Power Supply Dimensions 115mm x 68mm x 32mm (includes mounting tabs) Operating Environment Indoor only Outputs Relay 1 (NO/NC option) Relay 2 (NO/NC option) Weigand (D1/D0) Door status Inputs Request to exit (REX) Device response time <1 sec

Application (Apple App Store)

Operating System	IOS
Version Requirement	11.04 > (updates available on app store)
Detection Speed	<1 sec
Biometrics	Facial Recognition (auto learning)
Biometrics Backup	Auto backup to iCloud (with WiFi connected)
Data Storage	Local (on iPad) or Cloud
Access Log	Viewed on iPad (local) or NoahFace Access portal (Cloud)
Audit Log Availability	90 Days
Bulk User Upload	CSV file transfer (template available on NoahFace Access portal)

iPads

Model	6th Generation - Mini, 9.7", Pro, 12"
Power supply	12watt standard install
	30watt for lighting cables over 2mts or Camera Zoom enabled
Access Log	Viewed on iPad (local) or NoahFace Access portal (Cloud)
Access Log Availability	90 Days
Mounting	Recessed wall dock (not included)
	Surface mount enclosure (not included)
Storage	32Gb – 512Gb based on usage requirements matrix
	Eg. 32Gb if less than 500 users with 1-100 entries per day; or
	256Gb if more than 500 users with 200-800 entries per day